



DIMENSIONS AND ENGINEERING DATA FOR SPACER TYPE COUPLING

COUPLING NO	KW/100 RPM	OD1	HUB LENGTH A	SPACER BETWEEN SHAFT END		COVER LENGTH W	GAP C	MAX BORE	PILOT BORE
				MIN	MAX				
BRC 201	0.45	105	35	76.20	95.25	57	3	29	10
BRC 202	0.75	127	35	76.20	203.20	65	3	40	12
BRC 203	1.50	127	41	88.90	215.90	65	3	42	16
BRC 204	2.25	159	54	101.60	215.90	66	3	58	16
BRC 206	3.35	178	62	112.00	215.90	85	3	54	16
BRC 207	4.85	190.5	73	114.30	330.20	85	3	64	16
BRC 208	7.10	222	80	127.00	330.20	87	3	78	25
BRC 209	9.35	244.5	83	139.70	330.20	87	3	92	25
BRC 210	13.80	267	90	177.80	406.40	87	3	108	25
BRC 211	26.50	276	102	203.20	406.20	138	5	102	38
BRC 213	33.90	324	120	203.20	406.20	157	5	123	50
BRC 214	48.50	236.5	140	203.20	406.20	137	5	126	50
BRC 215	67.50	381	159	228.50	406.20	159	5	146	50
BRC 217	93.50	425	181	254.00	406.20	161	5	167	50