



Coupling NO.	Rating HP/RPM	Types DC, DP, DCV and DPV										Types DP, and DPV			Types DC, DCV			Brakewheel			Standard Brakewheel							
		Free hub length		Hub Length	Cover bore	Gap	Max. recess dia. RD	Stock rough bore	Max. bore		Cover dia.	Removal space RS	Safe speed			Cover dia.	Removal space RS	Safe speed	Type zz		Type yy		Type xx	Face dia. FD	Max. face width FW	Position P	Types	Coupling No.
		DP L1 (MM)	DPV L2 (MM)	L2 (MM)	CB (MM)	G (MM)	(MM)	(MM)	MB1 (MM)	MB2 (MM)	OD (MM)	RS (MM)	DPc (RPM)	DPn (RPM)	DPcs (RPM)	OD (MM)	RS (MM)	(RPM)	Min. face dia. FD (MM)	Position P (MM)	Min. face dia. FD (MM)	Position P (MM)	Min. face dia. FD (MM)	(MM)	(MM)	(MM)	(MM)	(MM)
212	.255	102	176	158	152.5	1.61	125	38	100	87	305	187	2050	3100	4100	-	129	1500	-	-	-	-	330	355 406 457	120 171 171	- XX XX	212	
213	.455	101.5	208	165	184	1.61	160	50	121	102	349	217	1875	2775	3875	333	149	1350	279	92	358	63.5	406	406 457 482 533	171 171 222 190	- XX XX XX	213	
214	.655	101.5	208	178	187.5	1.61	158	50	123	108	362	217	1750	2550	3650	346	149	1275	279	92	380	63.5	406	406 457 482	171 171 222	- XX XX XX	214	
215	.905	114	208	191	219	1.61	185	50	136	120	400	217	1525	2275	3175	384	149	1150	330	92	406	63.5	432	457 482 533 584	171 222 190 286	- XX XX XX XX	215	
217	1.255	127	208	191	244.5	1.61	204	50	162	137	438	217	1375	1975	2875	426	150	1050	355	92	457	63.5	483	457 482 533 584	171 222 190 286	- XX XX XX XX	217	
218	1.650	139	214	203	266.5	1.61	245	70	175	156	475	241	1300	1775	2675	462	163	950	-	-	-	-	510	533 584	190 286	- XX XX XX	218	
219	2.000	152	214	203	308	1.61	250	70	175	173	533	241	1250	1725	2525	517	163	900	-	-	-	-	584	584 609 762	286 190 216	- XX XX XX XX	219	

BOSON ENGINEERING
ENGINEERS & MANUFACTURES

CONTACT US:

OFFICE : 4/19 G.T. ROAD (SOUTH) HOWRAH- 711101

MOBILE : 9830226942. PHONE : (033)2666 1263, FAX : (033)2666 2935,

e-mail : k.basu@bosonengg.com, website : www.bosonengg.com